# HEATER PARTS

#### **HOSE & ACCESSORIES**

# **Drain Hose Fittings**



**8530**1/2" Hose x 1/2" Hose
Drain Hose Fitting - 90° Elbow



In-line T-Splicer (Plastic)
1/2" x 1/2" x 1/2"



8532 Duck Bill 5/8" hole size



8533 Check Valve 1/2" Hose Plastic

## **Duct Hose Fittings**



8550 Step-Up Splicer Connects 2 1/2" hose to 3" hose



8551 Step-Up Splicer Connects 2" hose to 2 1/2" hose



8555 T-Splicer For 2 1/2" duct hose



8557 T-Splicer with Shut-Off Door 2 1/2" hose Pull lever to shut-off air flow

## Hose Mounting Grommets (used when routing hose throught bulkheads or firewalls)



Dual Hose Grommet #6-#8 & #10-#12 3" Diameter Fits 2" hole



8541 Multi-size Hose Grommet 4" Diameter Hole opens to 3"



**8542** Flush Mount Grommet 2 <sup>1</sup>/<sub>8</sub>" Diameter



8543 Mount Grommet Fits 2" hole for #6 thru #10



8544 Mount Grommet Fits #6 thru #12

## **Hose Mount Clamps**



Hose Size	I.D.	PART#
#6 Single Clamp	<sup>3</sup> /4" dia.	4101
#8 Single Clamp	<sup>29</sup> / <sub>32</sub> " dia.	4102
#10 Single Clamp	1" dia.	4103
Double Clamp		4104

## Hose Clamps



Hose Size	I.D.	PART#
#6 - #8	5/16" - 13/32"	4106
#10 - #12	1/2" - 5/8"	4110

## Hose Cutter



8730
Handi-Cut A/C Hose Cutter
Makes quick clean cuts.
Cuts R12, R134a, barrier and
non-barrier hoses up to 1 1/2" OD.
8731 - Replacement Blade

© 2009 MEI Corporation 387

#### **Duct Hose**



Diameter	PART#	
2"	8520	9 ft.
2 1/2"	8521	9 ft.
3"	8522	9 ft.
3 1/2"	8523	9 ft.

## Evaporator Drain Hose



Diameter	PART #	ŧ
7/16"	8528	10 ft.

#### Heater Hose - Parker



Size	PART #				
5/8"	8800	50 ft.			
5/8"	8802	500 ft.			

#### ADD-ON A/C HOSE INSTALLATION KITS

#### FOR UNITS WITH RADIATOR OR REMOTE MOUNTED CONDENSER

Part No.	Hose Length & Size	Includes
(with Atco	18 ft., #6 & #10, 6 ft., #8 type fittings)	All fittings with R134a service ports, high and Low pressure switches, drier and Mounting backet, Assortment of hose ties and Rubber clamps.
9850EZ (with EZ Clip type fittings)		Same as above with EZ Clip pliers



#### FOR ROOF UNITS ONLY

Γ	Part No.	Hose Length & Size	Includes	
	9855 20 ft., #8 & #10 (with Atco type fittings)		Fittings (with R134a Service Ports)	
	9855EZ (with EZ Cli	ip type fittings)	Same as above with EZ Clip pliers	



### **HOSE**

# AeroQuip E-Z Clip Refrigerant Hose **GH134 SERIES**

See page 355 for E-Z Clip Fittings.



E-Z Clip Fittings work exclusively with Aeroquip GH 134 Series Refrigerant Hose Only.

Size	I.D.	O.D.	PAR1	Γ#	PART	# OPS
#6	5/16"	9/16"	8576	50 ft. Roll	8676	560 ft. Reel
#8	13/32"	11/16"	8578	50 ft. Roll	8678	575 ft. Reel
#10	1/2"	25/32"	8570	50 ft. Roll	8670	550 ft. Reel
#12	5/8"	63/64"	8572	50 ft. Roll	8672	367 ft. Reel
#16	7/8"	1 <sup>15</sup> /64"	8574	50 ft. Roll		
#16	7/8"	1 <sup>15</sup> /64"	8674	75 ft.		



#### HOSE

## Goodyear 4826 Refrigerant Hose


See page 338 for BeadLock Fittings.

#### **REDUCED OZONE PERMEATION**

Internal Nylon Barrier hose is specifically designed to reduce the permeation level of ozone depleting refrigerant and chemicals in heavy duty air conditioning systems.

#### UNIVERSAL COMPATIBILITY

Extensive testing has shown Barrier Hose to be compatible with R-12 and R-134a.



Size	I.D.	O.D.	PART	- #	PART	#	PAR	T # UPS
#6	5/16"	3/4"	8506	50 ft.	8620	250 ft.	8606	825 ft. Reel
#8	13/32"	29/32"	8508	50 ft.	8621	250 ft.	8608	725 ft. Reel
#10	1/2"	1"	8510	50 ft.	8622	250 ft.	8610	700 ft. Reel
#12	5/8"	1 1/8"	8512	50 ft.	8623	250 ft	8612	525 ft. Reel

NOTE: FOR USE WITH PUSH-ON OR BEAD LOCK (BUBBLE CRIMP) TYPE FITTINGS ONLY!!

## Goodyear 4860 Refrigerant Hose **Reduced Diameter**

See page 349 for Reduced Diameter Fittings.



Reduced barrier hose has thinner-wall construction that offers improved flexibility and reduced weight without sacrificing permeation resistance and burst strength.

Size	I.D.	O.D.	PART #	PART # UPS
#6	<sup>5</sup> /16"	39/64"	8514 50 ft. Roll	8614 550 ft. Reel
#8	13/32"	45/64"	8515 50 ft. Roll	8615 400 ft. Reel
#10	1/2"	25/32"	8516 50 ft. Roll	8616 300 ft. Reel
#12	5/8"	61/64"	<b>8517</b> 50 ft. Roll	8617 250 ft. Reel

## Parker/Futura™ Refrigerant Hose

See page 338 for BeadLock Fittings.

- For mobile R12 and R143a systems
- Meets or exceeds all SAE J2064 performance requirements



Siz	e I.D.	O.D.	PART #		PAR	Γ# UPS
#6	5/16"	3/4"	8556	50 ft. Roll	8656	600 ft. Reel
#8	13/32"	29/32"	8558	50 ft. Roll	8658	600 ft. Reel
#10	1/2"	1"	8560	50 ft. Roll	8660	500 ft. Reel
#12	5/8"	1 1/8"	8562	50 ft. Roll	8662	400 ft. Reel

## Parker/Guardian Barrier™ Refrigerant Hose **Reduced Diameter**

See page 349 for Reduced Diameter Fittings.



- · Kink resistance and excellent flexibility
- Improved resistance to vibration
- Noise dampening capabilities
- RP = new reduced permeation

					Bend
Size	I.D.	O.D.	PART	- #	Radius
#6	5/16"	.580"	8586	50 ft. Roll	2.32"
#8	13/32"	.680"	8588	50 ft. Roll	2.72"
#10	1/2"	.765"	8590	50 ft. Roll	3.00"
#12	5/8"	.930"	8592	50 ft. Roll	3.72"

